



## PATENT ABSTRACTS OF JAPAN

(11) Publication number: **04017843 A**(43) Date of publication of application: **22.01.1992**(51) Int. Cl. **A61B 8/12**

A61B 5/02, A61B 8/14, G01N 29/22, G06F 15/62

(21) Application number: **02122706**(71) Applicant: **OLYMPUS OPTICAL CO LTD**(22) Date of filing: **10.05.1990**(72) Inventor: **YAMAMOTO KATSUYUKI**(54) **ULTRASONIC DIAGNOSTIC APPARATUS**

## (57) Abstract:

**PURPOSE:** To obtain much information effective for diagnosis by arranging an ultrasonic probe to be inserted into a vessel, an ultrasonic transmitting/receiving section which irradiates a vessel wall with an ultrasonic wave while receiving an echo signal from the vessel wall, a tomographic image generation means to generate a tomographic image of the vessel wall by the echo signal and a quantitatively measuring means to determine at least one of a vessel section are, a vessel diameter, a thickness of the vessel wall and a beating-oriented change thereof.

**CONSTITUTION:** A cable driver is actuated to reciprocate an ultrasonic vibrator 5 spirally within an ultrasonic probe head 3 while an ultrasonic pulse is applied through a signal line to irradiate the internal wall of a blood vessel with an ultrasonic wave from the ultrasonic vibrator 5. The ultrasonic vibrator 5 receives an echo from a part to be observed and outputs it to a distance calculation circuit 31 and a tomographic image generation circuit 32, which 32 generates a tomo-

graphic image of the blood vessel from the echo signal. The tomographic image signal is applied to a monitor device 33 and a tomographic image is displayed on a display screen thereof. Furthermore, the tomographic image signal is applied to a thickness calculation circuit 35 through a heart beat synchronization type image input circuit 34 and thus, the thickness calculation circuit 35 outputs a tube thickness signal  $h(\theta)$  free from effect of heart beats to the monitor device 33.

COPYRIGHT: (C)1992,JPO&amp;Japio

